



Fachartikel

Belt Conveyor Transition Geometry

Bearbeitet von am 27. Nov. 2023

[Published in bulk solids handling, Vol. 2 \(1982\) No. 4](#)

This paper has been prepared to provide some practical formulae for selecting minimum transition lengths in belt conveyors and the geometry of the intermediate transition idlers. The geometry of any type of three roll idler is investigated for transitions where the pulley is (a) mounted at the belt line or (b) where it is raised above the belt line, so that there will be equal stress in the edge and centre sections of the belt. The theory is based on the basic assumptions that; there will be areas of low tension and areas of high tension within the transition; the average belt stress prior to the transition will be equal to the average tension within the transition.

The minimum transition length is given as a function of idler geometry, the elastic modulus of the belt and the high and low belt tensions within the transition.

By stipulating high and low tension limits as a function of the ultimate belt strength and by accepting that the elastic modulus can be expressed as a function of the ultimate belt strength, the derived formulae can be simplified and graphs of transition length versus belt tension can be produced.

At the head and tail ends of the conveyor there is a transition where the belt profile changes from the flat to troughed form. The distance over which this change takes place is known as the transition length. Within the transition the stress in some sections of the belt will increase and in other sections it will

decrease. The transition length must therefore be adequate to keep the high and low stresses within acceptable limits.

The importance of correct design of the belt transition is often overlooked by engineers and many transitions are either too short, causing distress to the belt, or the belt is incorrectly supported by the transition idlers, so that the belt is bent around only one idler. Photographs 1 and 2 show transitions on two conveyors which illustrate these problems.

Information relating to the minimum transition length varies considerably between manufacturers manuals and other text books. There is also an International Standard ISO 5293 1981 (E) which gives formulae for the transition length on three equal length idlers. This ISO Standard and most of the information in manuals and text books appears to be based on incorrect assumptions regarding the belt stresses in the transition area. There is therefore a need for some general formulae which reflect the actual stress conditions and these formulae should also be applicable to idlers which do not necessarily have three equal length rollers.

This document has been prepared to give engineers and draftsmen an understanding of both the theory of transition geometry and some practical formulae which will assist the designer in selecting the correct transition length and the form of the intermediate transition idlers.