

# TABLE OF CONTENTS

## **1. Introduction**

## **2. Pipe Size Optimization Study Report**

- 2.1 Objective
- 2.2 Design Methodology
- 2.3 Transition and Deposition Velocity Study
- 2.4 Pipeline Corrosion and Wear allowance
- 2.5 Optimization Results
- 2.6 Steady State Hydraulic Reports considering HDPE, Rubber-lined and CS Pipelines
- 2.7 Comparative study of HDPE, Rubber-lined and CS Pipeline
- 2.8 System Comparison considering Single and Multiple Pump Stations
- 2.9 Preliminary Cost Comparison
- 2.10 Conclusion and Finalization of Pipe Type, Pipe OD & ID and Preliminary Wall Thickness

## **3. Process Design Basis**

- 3.1 Operating Range Diagram
- 3.2 Orifice Chokes

## **4. Pump Selection and KW Requirement**

## **5. Transient State Hydraulic Analysis**

- 5.1 System Description
- 5.2 Pipeline Operating Philosophy Overview
- 5.3 Pipeline Control Philosophy Overview
- 5.4 Pipeline Overpressure Protection Strategy
- 5.5 Pipeline transient pressure modeling
- 5.6 Transient Pressure Analysis Computer Model
- 5.7 Modeling Basis
  - 5.7.1 Pipeline Allowable Transient Pressure
  - 5.7.2 Inline Valve Specifications
- 5.8 Simulation Scenarios and Procedure
- 5.9 Modeling Results

- 5.9.1 Normal and Emergency Shutdowns
- 5.9.2 Power Failure Event at Station
- 5.9.3 Accidental Valve Closure at Terminal
- 5.9.4 Batching Operation Simulation
- 5.9.5 Wall Thickness Optimization Based on Transient Simulation Results

## **6. Final Pipe Wall Thickness Determination**

## **7. Pipeline Operating Philosophy Requirements**

## **8. Capital Cost**

- 8.1 General Criteria
- 8.2 Direct Costs
- 8.3 Indirect Costs

## **9. Pipeline Construction Criteria**

## **10. Operating Cost**

## **11. Total Cost**

### **List of Tables:**

**Table 1** Details of optimum pipe and pump configuration

**Table 2** Performance of slurry pipeline during its life time

### **List of Figures**

**Fig. 1** Hydraulic Gradient Line (HGL) at Year 0 and EOL with slurry pipeline profile

**Fig. 2** Operating Range Diagram

**Fig. 3** Pipe Wall Thickness Diagram Based on Steady State Simulation Results

**Fig. 4** Transient Head Diagram for Pipeline Normal Shutdown

**Fig. 5** Transient Head Diagram for Pipeline Emergency Shutdown

**Fig. 6** Transient Head Diagram for Power Failure At Pump Station

**Fig. 7** Transient Head Diagram for Accidental Valve Closure at Terminal

**Fig. 8** Transient Head Diagram for Water Batch

**Fig. 9** Wall Thickness Optimization Based on Transient Simulation Results